

Chassis	Typ	Modell	Gesamtgewicht kg	Achslasten		max. HA kg	bar	Bereifung	
				max. VA kg	bar			Achse 1	Achse 2
Fiat (Original)	light	Tourer, Malibu RM	3500	1850	4,20	2000	4,50	215/70R15CP109Q	215/70R15CP109Q
Fiat (Original)	light	Tourer, Malibu RM	3650	1850	4,20	2000	4,50	215/70R15CP109Q	215/70R15CP109Q
Fiat (Original)	light	Tourer, Malibu RM	3500	1850	3,30	2000	3,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (Original)	light	Tourer, Malibu RM	3650	1850	3,30	2000	3,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (Original)	heavy	Tourer, Malibu RM	3500	2100	4,25	2400	5,00	225/75R16CP116Q	225/75R16CP116Q
Fiat (Original)	heavy	Tourer, Malibu RM	4250	2100	4,25	2400	5,00	225/75R16CP116Q	225/75R16CP116Q
Fiat (Original)	light	Malibu Van	3300	1750	3,90	1900	4,30	215/70R15CP109Q	215/70R15CP109Q
Fiat (Original)	light	Malibu Van	3500	1850	4,00	2000	4,40	215/70R15CP109Q	215/70R15CP109Q
Fiat (Original)	light	Malibu Van	3650	1850	4,00	2000	4,40	215/70R15CP109Q	215/70R15CP109Q
Fiat (Original)	light	Malibu Van	3500	1850	3,30	2000	3,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (Original)	light	Malibu Van	3650	1850	3,30	2000	3,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (AL-KO)	light	C-Line, Tourer	3500	1850 / (2000 mit Spiralfeder VA)	4,20 / 4,60	2000	4,60	215/70R15CP109Q	215/70R15CP109Q
Fiat (AL-KO)	light	C-Line, Tourer	3850	1850 / (2000 mit Spiralfeder VA)	4,20 / 4,60	2000	4,60	215/70R15CP109Q	215/70R15CP109Q
Fiat (AL-KO)	light	C-Line, Tourer	3500	1850 / (2000 mit Spiralfeder VA)	3,30/3,75	2000	3,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (AL-KO)	light	C-Line, Tourer	3850	1850 / (2000 mit Spiralfeder VA)	3,30/3,75	2000	3,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (AL-KO)	heavy	E-Line, C-Line, Tourer	3500	2100 / (2300 mit Spiralfeder VA)	4,00 / 4,30	2500	4,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (AL-KO)	heavy	E-Line, C-Line, Tourer	4250 / 4500	2100 / (2300 mit Spiralfeder VA)	4,00 / 4,30	2500	4,75	225/75R16CP116Q	225/75R16CP116Q
Fiat (AL-KO)	heavy	E-Line	4800	2300	4,30	2700	5,00	225/75R16CP116Q	225/75R16CP119Q
Fiat (AL-KO)	heavy (3-A)	E-Line, C-Line	5000	2100	4	1600 + 1600	3,5	225/75R16CP (C)116Q	225/75R16CP (C)116Q
Fiat (AL-KO)	heavy (3-A)	E-Line	5400	2300	4,3	1600 + 1600	3,5	225/75R16CP (C)116Q	225/75R16CP (C)116Q
Iveco Daily	C50	S-Plus	5600 / 5800	2100	4,75	3700	4,5	195/75R16C110/108N	195/75R16C110/108N
Iveco Daily	C50	S-Plus	5600 / 5800	2300 (Alufelgen 9-Loch)	4,75	3700	4,5	225/65R16C112/110N	195/75R16C110/108N
Iveco Daily	C50	S-Plus	5600 / 5800	2300 (Alufelgen 6-Loch)	4,5	3700	4,5	235/65R16C115/113N	195/75R16C110/108N
Iveco Daily	C60/C65	Highliner	6500	2400 / (2600 mit Fahrwerkspaket)	4,60 / 5,00	4550	4,60	225/75R16C118/116N	225/75R16C118/116N
Iveco Daily	C60/C65	Highliner	6700	2400 / (2600 mit Fahrwerkspaket)	4,60 / 5,00	4690	4,80	225/75R16C118/116N	225/75R16C118/116N
Iveco Daily	C70	Highliner	7000	2500	4,80	4900	4,90	225/75R16C121/120N	225/75R16C121/120N
Iveco Daily	C70	Highliner	7490	2800 (Alufelgen 6-Loch)	5,50	5240	5,30	225/75R16C121/120N	225/75R16C121/120N

Alte Modelle

Iveco Daily	C60/C65	Liner	6500	2400 / (2600 mit Fahrwerkspaket)	4,60 / 5,00	4550	4,60	225/75R16C118/116N	225/75R16C118/116N
Iveco Daily	C60/C65	Liner	6800	2400 / (2600 mit Fahrwerkspaket)	4,60 / 5,00	4740	4,80	225/75R16C118/116N	225/75R16C118/116N

MAN	TGL	Liner	7490	4000	7,50	5240	5,00	235/75R17,5 132/130K	235/75R17,5 132/130K
MAN	TGL	Liner	8800	4000	7,50	5600	5,25	235/75R17,5 132/130K	235/75R17,5 132/130K
MAN	TGL	Liner	10000	4000	7,50	6800	6,75	245/70R17,5 134/132K	245/70R17,5 134/132K
MAN	TGL	Liner	12000	4400	8,25	8400	8,40	245/70R17,5 136/134K	245/70R17,5 136/134K

* Die dargestellten Reifendrucke sind unverbindlich und stammen gemäß maximaler Achslast aus ausgewählten Reifendrucktabellen.

Stand 11/2017 Änderungen vorbehalten